

ARP Fly wheel bolt, product and torque information 2019V1

While great care has been taken to ensure the accuracy of all information, **THE STARTING GRID** cannot be held responsible for mistakes and errors, whatsoever.

Car make and model:	Part#	Thread and Pitch	Under Head Length	Threaded length	Wrench size	Head height	Shaft diameter	Quantity	Torque Nm*	Picture
BMC										
1600cc A-Series	206 - 2802	3/8 - UNF	22,9	17,8	9/16"	5,3	9,5	6	54,6	http://arpcatalog.com/i/7.1/800/206-2802.jpg
Rover K-Serie flanged head	206 - 2803	M10 x 1	21	17,1	12	9	-	6	0,0	http://arpcatalog.com/i/7.1/800/206-2803.jpg
BMW										
2,3l (S14)	201 - 2801	M12 x 1,5	22,2	13	19	6,3	11	8	143,3	http://arpcatalog.com/i/7.1/800/201-2801.jpg
2,3L (S14) (ZMS)	201 - 2802	M12 x 1,5	28,2	14,5	19	6,2	11	8	143,3	http://arpcatalog.com/i/7.1/800/201-2802.jpg
Mini N12, 4 Cyl, 1,6l	101 - 2801	M9 x 1,25	20,4	20,4	16	5,2	-	6	68,3	http://arpcatalog.com/i/7.1/800/101-2801.jpg
CHEVROLET										
90° V6 & 265-454 V8, 2 Crankshaft seal	200 - 2802 Pro	7/16" - UNF	25,4	20,3	3/4"	6,2	11,2	6	95,6	http://arpcatalog.com/i/7.1/800/200-2802.jpg
	100 - 2801 High								84,6	http://arpcatalog.com/i/7.1/800/100-2801.jpg
90° V6 & 305-502 V8,1 Crankshaft seal	200 - 2807	7/16" - UNF	25,4	-	-	-	-	-	0,0	http://arpcatalog.com/i/7.1/800/200-2807.jpg
LS-Series	244 - 2901	M11 x 1,5	22,5	22	3/4"	6,2	-	6	81,9	http://arpcatalog.com/i/7.1/800/244-2901.jpg
Gen III/LS Ser. small block	330 - 2802	M11 x 1,5	22,4	16	1/2"	9,2	11,2	6	81,9	http://arpcatalog.com/i/7.1/800/330-2802.jpg
V8 with TILTON Flywheel, use 1/2" socket	330 - 2801	7/16" - UNF	22,2		1/2"	8,9	11,2	6	81,9	http://arpcatalog.com/i/7.1/800/330-2801.jpg

Car make and model:	Part#	Thread and Pitch	Under Head Length	Threaded length	Wrench size	Head height	Shaft diameter	Quantity	Torque Nm*	Picture
SL6, 3,9l V6 & 273,-440 V8, 6 bolt crank	240 - 2801	7/16" - UNF	22,2	-	-	-	-	-	0,0	http://arpcatalog.com/i/7.1/800/240-2801.jpg
Aftermarket 383-440 V8 & Hemi 8 bolt crank	245 - 2801	1/2 - UNF	22,2	-	-	-	-	-	0,0	http://arpcatalog.com/i/7.1/800/245-2801.jpg
Chevy	100 - 2901	7/16" - UNF	17,3	14	3/4"	6,3	-	6	0,0	-
DODGE										
Hemi 5 7/6 1L Flexplate	147 - 2902	M10 x 1	17,7	15	5/8" / 16 mm.	5,2	10	8	95,6	-
FORD										
Mustang 86-95, 5,0 ltr	150 - 2202	M8 x 1,25	20	20	10	7,6			0,0	http://arpcatalog.com/i/7.1/800/150-2202.jpg
1,8- & 2,0l Duratec	251 - 2802	M12 x 1	25,2	20	19	6,2	11,9	6	116,0	http://arpcatalog.com/i/7.1/800/251-2802.jpg
Pinto 2+2,3ltr	251 - 2901	M10 x 1	20,5	20,5	16	5,4	w/o	6	95,6	http://arpcatalog.com/i/7.1/800/251-2901.jpg
2,0l Zetec	251 - 2801	M11 x 1	22,9	19,1	3/4"	6,2	11	6	95,6	http://arpcatalog.com/i/7.1/800/251-2801.jpg
2000cc Pinto	151 - 2801	M10 x 1	29,2	20,3	5/8"	5,2	10	6	66,9	http://arpcatalog.com/i/7.1/800/151-2801.jpg
8,8" & 9"	250-3003	7/16" - UNF	19	11	3/4"	6,2	11,05	10	116,0	
Cosworth YB (2,0l)	251 - 2803	M10 x 1	29,2	21,5	5/8"	5,3	10	9	95,6	http://arpcatalog.com/i/7.1/800/251-2803.jpg
4,6l & 5,4l modular V8 Flexplate	254 - 2901	M10 x 1	20,3	18	5/8"	5,2	w/o	8	95,6	http://arpcatalog.com/i/7.1/800/254-2901.jpg
4,6l & 5,4l modular V8	254 - 2801 similar to 147 - 2801	M10 x 1	25,4	18,5	5/8"	5,2		8	66,9	http://arpcatalog.com/i/7.1/800/254-2801.jpg
289-460 V8	200 - 2802 Pro	7/16" - UNF	25,4	20,3	3/4"	6,2	11,2	6	95,6	http://arpcatalog.com/i/7.1/800/200-2802.jpg
	100 - 2801 High								84,6	http://arpcatalog.com/i/7.1/800/100-2801.jpg

Car make and model:	Part#	Thread and Pitch	Under Head Length	Threaded length	Wrench size	Head height	Shaft diameter	Quantity	Torque Nm*	Picture
351 Nascar V8 3/4" socket	350 - 2802	7/16" - UNF	23,5	18,4	3/4"	6,4	11,1		0,0	http://arpcatalog.com/i/7.1/800/350-2802.jpg
V8 with Tilton FWY 1/2" socket	350 - 2801	7/16" - UNF	24,1	15,2	1/2"	8,9	11,2	6	102,4	http://arpcatalog.com/i/7.1/800/350-2801.jpg
V8 with Tilton FWY 3/4" socket	95-975-6	7/16" - UNF	20,3	15	3/4"	6,3	11,2		0,0	
Mustang PBK	150 - 2202	M8 x 1,25	20	20	10	7,5		6	No- information	http://arpcatalog.com/i/7.1/800/150-2202.jpg
Coyote 5,0L	156 - 2801	M10 x 1	25	17	3/4"	6,4	10	8	95,6	-
HONDA										
1,5l & 1,6l OHC, D-Series	208 - 2801	M12 x 1	25,2	20	3/4"	6,2	11,9	6	116,0	http://arpcatalog.com/i/7.1/800/208-2801.jpg
1,6l, 1,7l, 1,8l & 2,0l DOHC, B-series	208 - 2802	M12 x 1	25,2	20	3/4"	6,2	11,9	6	116,0	http://arpcatalog.com/i/7.1/800/208-2802.jpg
LANCIA										
Stratos	209 - 2801	M10 x 1,25	25	17	3/4"	6,3		8	79,2	http://arpcatalog.com/i/7.1/800/209-2801.jpg
MITSUBISHI										
4G63 nach Bj. 93	107 - 2801	M12 x 1,25	21	15	3/4"	6,3	12	7	130	http://arpcatalog.com/i/7.1/800/107-2801.jpg
4B11	207 - 2801	M12 x 1,26	18	18	3/4"	6,2	w/o	7	130	http://arpcatalog.com/i/7.1/800/207-2801.jpg
2,0L 4G63 Evo 4-9	107 - 2803	M12 x 1,27	15,5	15,5	3/4"	6,2	w/o	7	130	-
NISSAN										
RB 26	102 - 2801	M12 x 1,25	30	20	3/4"	6,2	12	6	130	-
OPEL										

Car make and model:	Part#	Thread and Pitch	Under Head Length	Threaded length	Wrench size	Head height	Shaft diameter	Quantity	Torque Nm*	Picture
2,0l	209 - 2801	M10 x 1,25	25	17	3/4"	6,3	-	8	95	http://arpcatalog.com/i/7.1/800/209-2801.jpg
PONTIAC										
Iron Duke 4 Zyl. (12 pcs)	291 - 2801	7/16" - UNF	19,3	19,3	7/16"	9,1	w/o	12	116,0	http://arpcatalog.com/i/7.1/800/291-2801.jpg
350-455 V8 including washers	291 - 2802	1/2 - UNF	25,4	14	3/4"	6,2	12,7	-	0,0	http://arpcatalog.com/i/7.1/800/290-2802.jpg
PORSCHE										
911 late	204 - 2801	M10 x 1,25	19,8	13,6	Inner Bi-Hex.	8,5	9,2	9	95,6	http://arpcatalog.com/i/7.1/800/204-2801.jpg
911 early	204 - 2802	M12 x 1,25	25,5	22	Inner Bi-Hex.	8,4	11,2	6	136,5	http://arpcatalog.com/i/7.1/800/204-2802.jpg
ROVER										
K-Series	206 - 2803	M10 x 1	21	17,1	12	9	10	-	0,0	http://arpcatalog.com/i/7.1/800/206 - 2803.jpg
TOP FUEL										
8740 including washer (200 Kpsi)	200 - 2804	1/2 - UNF	25,4	15,2	3/4"	6,4	12,7		0,0	http://arpcatalog.com/i/7.1/800/200 - 2804.jpg
L19 including washer (260 Kpsi)	200 - 2805	1/2 - UNF	25,4	15,2	3/4"	6,4	12,7		0,0	http://arpcatalog.com/i/7.1/800/200-2805.jpg
TOYOTA										
1,6l (4AGE, 2JZ-GTE) DOHC (8pcs)	203 - 2802	M10 x 1,25	26,7	20,3	1/2"	8,9	10		0,0	http://arpcatalog.com/i/7.1/800/203-2802.jpg
2,0L (3SGTE)DOHC (8pcs)	203 - 2801	M12 x 1,25	25,4	20,3	3/4"	6,2	12	8	116,0	http://arpcatalog.com/i/7.1/800/203-2801.jpg

Car make and model:	Part#	Thread and Pitch	Under Head Length	Threaded length	Wrench size	Head height	Shaft diameter	Quantity	Torque Nm*	Picture
2,2l (2OR) & 2,4 l (22R)	203 - 2803	M11 x 1,25	26,4	20,3	5/8"	5,2	11	6	79,2	http://arpcatalog.com/i/7.1/800/203-2803.jpg
1,8l 2ZZGE 4Zyl.	103 - 2802	M10 x 1,25	22,4	17,8	5/8"	5	10	8	95,6	http://arpcatalog.com/i/7.1/800/103-2802.jpg
SUBARU										
FA20	260 - 2801	M10 x 1	23,5	16	5/8" / 16 mm.	5,3	9,95	8	82,0	-
SUZUKI										
M16A 1,6l, 4Cyl.	171 - 2801	M10 x 1,25	19,2	13,1	5/8"	5,2	10	8	95,6	http://arpcatalog.com/i/7.1/800/171-2801.jpg
VOLKSWAGEN										
VR 6 / V6 R32	251 - 2901**	M10 x 1	20,5	20,5	16	5,4	w/o	10	96	**Six bolt set.
GENERAL										
Tilton Bolt Kit (gleich 330 - 2801)	657 - 952	7/16" - UNF	22,2	17,1	1/2"	8,9	11,2	-	0,0	-